



# AG HOSES

**Pressure**

Size inch mm	Working psi kpa	Burst psi kpa	End Tensile Strength lbs kg	Wall Thickness inch mm	Weight lbs/ft kg
<b>MAINLINE™</b>					
7.25 184	250 1724	500 3447	70,000 31750	.18 4.57	1.9 .86
8 203	250 1724	500 3447	80,000 36287	.18 4.57	2.1 .95
10 254	250 1724	500 3447	96,000 43545	.2 5.08	2.85 1.29
<b>ARMOUR GUARD®</b>					
4 100	300 2068	600 4136	25,000 11340	.12 3.05	.84 0.38
5 125	300 2068	600 4136	36,000 16329	.125 3.18	1.04 0.47
6 150	300 2068	600 4136	54,000 24494	.13 3.30	1.48 0.67
<b>PREMIUM 200®</b>					
3 75	300 2068	600 4136	20,000 9072	.115 2.92	.60 .27
4 100	300 2068	600 4136	25,000 11340	.12 3.05	.84 .38
4.5 114	300 2068	600 4136	32,000 14515	.15 3.80	1.2 .56
5 125	300 2068	600 4136	36,000 16329	.125 3.18	1.04 .47
<b>DRAG HOSE™</b>					
5 125	250 1724	500 3447	40,000 18143	.14 3.56	1.15 0.52
5-1/2 140	250 1724	500 3447	46,000 20865	.145 3.68	1.26 0.57
6 150	250 1724	500 3447	46,000 20865	.155 3.94	1.45 0.66
7-1/4 184	250 1724	500 3447	70,000 31750	.18 4.57	1.89 0.86



BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.



**Step up your fluid delivery!**

Contact us today: 833.655.9201 · bulldoghose.com