



**Bulldog**  
HOSE COMPANY



# ARMOUR GUARD® LDH

## Heavy-Duty, Rubber-Covered Industrial Discharge Hose

Transfer sludge and manure easily and reliably with the Bulldog Armour Guard® Hose. Designed to be a lay-flat, flexible discharge hose that brings impressive flow to any situation. It combines the lightweight, compact features of a unique nitrile/PVC blend with enhanced durability and abrasion resistance as compared to a conventional rubber hose. Armour Guard features a heavy-duty, one-piece design with all-synthetic, extruded-through-the-weave materials. This allows the hose to expand under pressure, decreasing friction loss and increases flow. The ozone-resistant synthetic rubber liner and cover totally encase and protect the high-performance synthetic woven reinforcement from the effects of abrasion, chemicals and heat. Armour Guard cleans easily and offers ease of maintenance. The standard color is yellow.

### UNIQUE DESIGN FEATURES:

- Lower friction loss
- Reduces pumping costs
- Higher flow rates and further pumping distance
- Fast deployment and retrieval



*Backed by Bulldog's  
Irrigation Hose One-Year Warranty.  
[bulldoghose.com/resources](http://bulldoghose.com/resources)*



**Step up your fluid delivery!**

Contact us today: 833.655.9201 · [bulldoghose.com](http://bulldoghose.com)

**AMERICAN MADE TOUGH.™**

## FEATURES:

### Long Service Life

Nitrile-rubber extruded through-the-weave provides long-term storage stability and working life. Superior resistance to ozone and ultraviolet light.

### Durable Construction

Special rib pattern for exceptional abrasion and cut resistance.

### High Pressure Rating

Fully protected high tensile yarns for improved working pressure rating and drag resistance.

### Kink Resistant

Superior kink resistance.

### Best in Class Adhesion

Best in class adhesion provides enhanced hose performance and increased hose life.

### Perfect for Supply Lines

Best used as a supply line, feeder line discharge applications.

### High Visibility

Yellow color yields a higher level of nighttime visibility.

### Multiple Sizes

Available in 4", 5" and 6" hand lines.

## TECHNICAL SPECIFICATIONS:

Size	Pressure		End Tensile Strength	Wall Thickness		Weight
	Working	Burst				
inch mm	psi kpa	psi kpa	lbs kg	inch mm	lbs/ft kg	
4 100	300 2068	600 4136	25,000 11340	.12 3.05	.84 0.38	
5 125	300 2068	600 4136	36,000 16329	.125 3.18	1.04 0.47	
6 150	300 2068	600 4136	54,000 24494	.13 3.30	1.48 0.67	

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.

