



# FIRE HOSES

**Pressure**

|                      | Size<br>inch mm | Standard<br>Color | Pressure           |                  |                  |                  | Bowl Size<br>inch | Coil<br>Diameter |            |
|----------------------|-----------------|-------------------|--------------------|------------------|------------------|------------------|-------------------|------------------|------------|
|                      |                 |                   | Service<br>psi kpa | Proof<br>psi kpa | Burst<br>psi kpa | Weight<br>lbs kg |                   | inch mm          |            |
| <b>HI-COMBAT II®</b> |                 |                   |                    |                  |                  |                  |                   | (50'/15M)        | (50'/15M)  |
| ULC                  | 1-3/4 45        |                   | 500 3500           | 1000 7000        | 1500 10500       | 2-1/8            | 18 8.1            | 16.5 419         |            |
|                      | 2 50            |                   | 500 3500           | 1000 7000        | 1500 10500       | 2-3/8            | 20 9.07           | 17.5 445         |            |
| ULC                  | 2-1/2 65        |                   | 500 3500           | 1000 7000        | 1500 10500       | 2-7/8            | 23 10.4           | 18.5 470         |            |
| <b>FIREPOWER II™</b> |                 |                   |                    |                  |                  |                  |                   | (50'/15M)        | (50'/15M)  |
| ULC                  | 1-3/4 45        |                   | 500 3500           | 1000 7000        | 1500 10500       | 2-1/8            | 18 8.1            | 16.5 419         |            |
|                      | 2 50            |                   | 500 3500           | 1000 7000        | 1500 10500       | 2-3/8            | 20 9.1            | 17.5 445         |            |
| ULC                  | 2-1/2 65        |                   | 500 3500           | 1000 7000        | 1500 10500       | 2-7/8            | 23 10.4           | 18.5 470         |            |
| <b>ULTIMA™</b>       |                 |                   |                    |                  |                  |                  |                   | (50'/15M)        | (100'/30M) |
| ULC                  | 1-1/2 38        | White             | 400 2800           | 800 5600         | 1200 8400        | 1-15/16          | 13 5.9            | 18 457           |            |
| ULC                  | 1-3/4 45        | White             | 400 2800           | 800 5600         | 1200 8400        | 2-1/8            | 15 6.8            | 18 457           |            |
|                      | 2 50            | White             | 400 2800           | 800 5600         | 1200 8400        | 2-2/5            | 17 7.7            | 19 483           |            |
| ULC                  | 2-1/2 65        | White             | 400 2800           | 800 5600         | 1200 8400        | 3                | 22 10.0           | 21 533           |            |
|                      | 3 75            | White             | 400 2800           | 800 5600         | 1200 8400        | 3-1/2            | 29 13.2           | 21 533           |            |
| <b>FIREGUARD™</b>    |                 |                   |                    |                  |                  |                  |                   |                  |            |
|                      | 1-3/4 45        |                   | 500 3500           | 1000 7000        | 1500 10500       | 2-1/8            |                   |                  |            |
| <b>HI-VOL®</b>       |                 |                   |                    |                  |                  |                  |                   | (100'/30M)       | (100'/30M) |
|                      | 3 75            | Yellow/Red        | 300 2100           | 600 4200         | 900 6300         | 3-5/16           | 60 27.2           | 25 635           |            |
| ULC                  | 4 100           | Yellow/Red        | 225 1575           | 450 3150         | 675 4725         | 4-5/32           | 84 38.1           | 24 610           |            |
| ULC                  | 5 125           | Yellow/Red        | 200 1400           | 400 2800         | 600 4200         | 5-3/8            | 104 47.2          | 27 686           |            |
|                      | 6 150           | Yellow            | 200 1400           | 400 2800         | 600 4200         | 6-15/32          | 148 67.1          | 32 813           |            |

Bulldog Hose Company maintains ongoing product improvement and development programs. Therefore Bulldog reserves the right to modify any product or specification without prior notice. If necessary, please contact Bulldog Hose Company customer service to ensure that all claims and technical data are current.



| Size<br>inch mm                       | Standard<br>Color | Pressure           |                  |                  |         | Bowl Size<br>inch | Weight<br>lbs kg | Coil<br>Diameter |  |
|---------------------------------------|-------------------|--------------------|------------------|------------------|---------|-------------------|------------------|------------------|--|
|                                       |                   | Service<br>psi kpa | Proof<br>psi kpa | Burst<br>psi kpa | inch    |                   |                  | inch mm          |  |
| <b>HI-VOL TPU™</b>                    |                   |                    |                  |                  |         |                   | (100'/30M)       | (100'/30M)       |  |
| 4 100                                 |                   | 200 1400           | 400 2800         | 600 4200         | 4-5/16  | 75 34.0           | 22               | 560              |  |
| 5 125                                 |                   | 200 1400           | 400 2800         | 600 4200         | 5-3/8   | 94 42.6           | 26               | 660              |  |
| <b>RED CHIEF® &amp; YELLOW CHIEF®</b> |                   |                    |                  |                  |         |                   | (50'/15M)        | (50'/15M)        |  |
| ULC 1-1/2 38                          | Red/Yellow        | 300 2100           | 600 4200         | 900 6300         | 1-13/16 | 14 6.4            | 14-3/4           | 375              |  |
| ULC 1-3/4 45                          | Red/Yellow        | 300 2100           | 600 4200         | 900 6300         | 2-1/16  | 18 8.2            | 14-3/4           | 375              |  |
| 2 50                                  | Red/Yellow        | 300 2100           | 600 4200         | 900 6300         | 2-5/16  | 22 10.0           | 16               | 406              |  |
| ULC 2-1/2 65                          | Red/Yellow        | 300 2100           | 600 4200         | 900 6300         | 2-7/8   | 26 11.8           | 16-1/2           | 419              |  |
| 3 75                                  | Red/Yellow        | 300 2100           | 600 4200         | 900 6300         | 3-13/32 | 30 13.6           | 16-1/2           | 419              |  |
| <b>FLOMASTER™</b>                     |                   |                    |                  |                  |         |                   | (50'/15M)        | (50'/15M)        |  |
| 1-1/2 38                              | Red               | 300 2100           | 600 4200         | 900 6300         | 1-13/16 | 16 7.2            | 18               | 457              |  |
| 1-3/4 45                              | Red               | 300 2100           | 600 4200         | 900 6300         | 2-1/16  | 19 8.6            | 18               | 457              |  |
| 2 50                                  | Red               | 300 2100           | 600 4200         | 900 6300         | 2-3/8   | 22 10.0           | 19               | 483              |  |
| 2-1/2 65                              | Red               | 300 2100           | 600 4200         | 900 6300         | 2-7/8   | 28 12.7           | 20               | 508              |  |
| 3 75                                  | Red               | 250 1800           | 500 3500         | 750 5200         | 3-1/4   | 29 13.2           | 20               | 508              |  |
| 4 100                                 | Red               | 250 1800           | 500 3500         | 750 5200         | 4-3/8   | 40 18.1           | 20               | 508              |  |
| 5 125                                 | Red               | 225 1600           | 450 3150         | 675 4725         | 5-3/8   | 52 23.6           | 21               | 533              |  |
| <b>HI-POWER™</b>                      |                   |                    |                  |                  |         |                   | (50'/15M)        | (50'/15M)        |  |
| ULC 1-1/2 38                          | Blue              | 300 2100           | 600 4200         | 900 6300         | 1-3/4   | 11 5.0            | 13               | 330              |  |
| ULC 1-3/4 45                          | Blue              | 300 2100           | 600 4200         | 900 6300         | 2-1/16  | 14 6.3            | 14               | 356              |  |
| 2 50                                  | Blue              | 300 2100           | 600 4200         | 900 6300         | 2-5/16  | 18 8.1            | 14               | 356              |  |
| ULC 2-1/2 65                          | Blue              | 300 2100           | 600 4200         | 900 6300         | 2-3/4   | 20 9.0            | 15               | 381              |  |
| <b>REDSKIN/BLUESKIN®</b>              |                   |                    |                  |                  |         |                   | (50'/15M)        | (50'/15M)        |  |
| 1-1/2 38                              |                   | 300 2100           | 600 4200         | 900 6300         | 1-3/4   | 11 5              | 13               | 330              |  |
| 1-3/4 45                              |                   | 300 2100           | 600 4200         | 900 6300         | 2-1/16  | 14 6.4            | 13-3/4           | 349              |  |
| 2 51                                  |                   | 300 2100           | 600 4200         | 900 6300         | 2-5/16  | 18 8.2            | 14-1/2           | 368              |  |
| 2-1/2 64                              |                   | 300 2100           | 600 4200         | 900 6300         | 2-3/4   | 22 10             | 14-1/2           | 368              |  |
| 3 76                                  |                   | 300 2100           | 600 4200         | 900 6300         | 3-5/16  | 30 13.6           | 16-1/2           | 419              |  |



**Raise your firefighting standards!**

Contact us today: 833.655.9201 · bulldoghose.com