



Fuel & Water Delivery Hose

WAT-HOG™

A premium flexible layflat hose designed for the transfer of fuel, wastewater, sewer, treated and reclaimed water. WAT-Hog™ features a unique "through-theweave" one piece construction comprising a circular woven high tenacity polyester reinforcement totally encapsulated in a tough elastomeric polyurethane cover and lining. Designed for long life and maintenance free service in even the harshest environments. High flexibility and kink resistance allows natural ground contours to be followed without putting stress on the pipeline and eliminates expensive path cutting work.

TYPICAL APPLICATIONS:

Municipal

- · Pipeline by-pass
- · Waste transfer
- · Testing/flushing water mains
- · Sewer and water treatment
- · Municipal fire services

Marine

- · Cargo loading/unloading
- · Supply ship to off shore facilities

Industrial

- · High flow dewatering
- · Liquid and powder transfer
- Slurry pumping
- Loading/unloading from truck
- · Industrial fire services
- · Portable chiller operation

Military

· Water transfer

Backed by BullDog's Industrial Hose Two-Year Warranty. bulldoghose.com/resources



Step up your fuel/water delivery!
Contact us today: 833.655.9201 · bulldoghose.com

WAT-HOG™



FEATURES:

Long Service Life

Designed for long life and maintenance free service in even the harshest environments. Tough and durable with exceptional resistance to abrasion and cutting for use on a wide variety of ground conditions. No corrosion or scaling. Resistant to fuels, chemicals, UV, ozone, weathering, hydrolysis, and microbiological attack.

Durable Construction

Features a unique "through-theweave" one-piece construction comprising a circular woven high tenacity polyester reinforcement totally encapsulated in a tough elastomeric polyurethane cover and lining.

Easy to Store and Transport

Long-term storage in coiled configurations will have minimal impact on hose life.

Additional Hardware

A wide range of couplings, manifolds, and hardware available for connecting the hose to additional segments, fluid supplies, or auxiliary hardware.

Low Operating Costs

A low-pressure loss for efficient pumping. Swells up to 10% above uncharged diameter at maximum operating pressure enabling more water to be pumped.

Fast Deployment and Retrieval

Long continuous lengths can be quickly deployed and retrieved using a wide variety of systems including light duty trailers, flaking boxes, and power-driven reels. High flexibility and kink resistance allows natural ground contours to be followed without putting stress on the pipeline and eliminates expensive path cutting work. Fewer and faster connections mean reduced labor and equipment costs.

TECHNICAL SPECIFICATIONS:

		Pressure				Wall				
Size		Working		Burst		Thickness		We	Weight	
inch	mm	psi	kpa	psi	kpa	inch	mm	lbs/ft	kg	
2	50	300	2100	600	4200	.08	2.03	.21	0.095	
2-1/2	65	300	2100	600	4200	.08	2.03	.30	0.136	
3	75	300	2100	600	4200	.09	2.28	.37	0.168	
4	100	300	2100	600	4200	.09	2.28	.56	0.254	
6	150	300	2100	600	4200	.1	2.54	1.22	0.553	
7-1/4	184	250	1800	500	3500	.16	4.06	1.89	0.859	
8	200	250	1800	500	3500	.18	4.57	2.1	0.95	
10	250	250	1800	500	3500	.2	5.08	2.85	1.29	

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact **BullDog Hose Company** customer service to ensure that all claims and technical data are current.



"THROUGH-THE-WEAVE" ONE-PIECE CONSTRUCTION PROVIDES EXTREME DURABILITY ON HARSH TERRAINS AS WELL AS HIGH FLEXIBILITY AND KINK RESISTANCE

